

### BLOCK UNIT Series

*Small built-in pressure boosters, fully automatic. These units consist of a single phase pump, diaphragm tank, pressure switch, pressure gauge and various connectors suitable for commercial water systems.*

*The units are fully assembled and ready to be connected to the building's water system.*

*Choice of units with self-priming (BGM) or horizontal single-impeller (CEAM) centrifugal pumps.*

#### SPECIFICATIONS

**Delivery:** up to 100 l/min (6 m<sup>3</sup>/h)

**Head:** up to 50 metres (5 bar)

**Power supply:** single-phase  
50 and 60 Hz

**Motor starting:** D.O.L.

**Power:** up to 1.1 kW.

**Water temperature:** 0°C to +40°C

**Pump type:** horizontal

**Control:** pressure switch

**Tank:** 24l horizontal cylindrical

#### MATERIALS

**Pump:** Stainless steel

**Tank:** Enamelled Steel; butyl membrane

#### APPLICATIONS

- Pressure boosting in water systems for domestic use, lawn sprinkling and washing
- Pumping of non-aggressive liquids in industrial plants



For a complete list of technical information, consult [www.lowara.com](http://www.lowara.com)

*Engineered for life*



## General Catalogue

### SPHERE UNIT, BLOCK UNIT SERIES TECHNICAL SPECIFICATIONS

Type	Rated Power		Input Current A	Set up bar	Flow l/min	Approximative Overall Dimensions in mm			Weight Kg
	kW	HP				A	B	Height H	
Grupposfera PM 16	0,3	0,4	2,4	1,4 - 2,8	10 - 37	390	470	635	14,4
Grupposfera PM 21	0,37	0,5	2,8	1,4 - 3,0	10 - 40	390	470	635	15,0
Grupposfera PM 30	0,5	0,7	4	2,0 - 3,5	10 - 50	390	470	635	16,5
Grupposfera PM 40	0,6	0,8	5,3	2,5 - 4,0	15 - 50	390	470	635	17,0
Grupposfera CEAM 70/3	0,37	0,5	2,7	1,2 - 2,0	30 - 80	390	580	720	17,0
Grupposfera CEAM 70/5	0,55	0,75	4,5	1,8 - 2,8	30 - 80	390	580	720	18,0
Grupposfera CEAM 80/5	0,75	1	4,8	1,8 - 2,8	30 - 100	390	580	720	19,0
Grupposfera CAM 70/33	0,75	1	5	2,4 - 3,8	30 - 80	390	470	720	21,0
Grupposfera CAM 70/34	0,9	1,2	6,2	3,2 - 4,3	30 - 80	390	470	720	23,0
Grupposfera CAM 70/45	1,1	1,5	8	3,6 - 5,2	30 - 80	390	470	720	25,0
Grupposfera CAM 120/33	1,1	1,5	7,5	3,0 - 4,0	50 - 150	390	470	720	25,0
Grupposfera CAM 120/35	1,5	2	9,9	3,2 - 4,6	50 - 150	390	470	720	30,0
Grupposfera CAM 120/55	2,2	3	11,7	4,2 - 5,6	50 - 150	390	470	720	32,0
Grupposfera CAM 200/33	2,2	3	10,8	3,0 - 4,0	80 - 210	390	470	720	32,0
Grupposfera BGM 3 *	0,55	0,75	3	1,9 - 3,0	10 - 50	390	580	720	17,0
Grupposfera BGM 5 *	0,55	0,75	4,3	2,5 - 3,5	10 - 60	390	580	720	18,0
Grupposfera BGM 7 *	0,75	1	5	2,8 - 4,1	20 - 60	390	580	720	19,0
Grupposfera BGM 9 *	0,9	1,2	5,6	3,2 - 4,2	20 - 65	390	580	720	20,0
Grupposfera BGM 11 *	1,1	1,5	6,5	3,4 - 4,7	20 - 70	390	580	720	21,0
Grupposfera 2HM3	0,3	0,4	2,3	1,2 - 2,0	20 - 70	390	470	720	14,0
Grupposfera 2HM4	0,45	0,6	2,9	2,0 - 3,3	20 - 70	390	470	720	14,0
Grupposfera 2HM5	0,55	0,75	3,7	3,2 - 4,4	20 - 70	390	470	720	15,0
Grupposfera 2HM7	0,75	1	5,1	3,6 - 5,6	20 - 70	390	470	720	15,0
Grupposfera 4HM4	0,45	0,6	2,8	1,2 - 2,0	40 - 120	390	470	720	15,0
Grupposfera 4HM5	0,55	0,75	3,8	1,8 - 3,0	40 - 120	390	470	720	15,0
Grupposfera 4HM7	0,75	1	5,7	2,4 - 4,0	40 - 120	390	470	720	18,2
Grupposfera 4HM9	0,9	1,2	6,5	2,8 - 5,0	40 - 120	390	470	720	18,2
Block CEAM 70/3	0,37	0,5	2,7	1,2 - 2,0	30 - 80	290	660	610	20,0
Block CEAM 70/5	0,55	0,75	4,2	1,8 - 2,8	30 - 80	290	660	610	21,0
Block CEAM 80/5	0,75	1	4,8	1,8 - 2,8	30 - 100	290	660	610	22,0
Block CEAM 210/4	1,5	2	8,6	1,2 - 2,2	120 - 300	290	660	610	26,0
Block CAM 70/33	0,75	1	5	2,4 - 3,8	30 - 80	290	660	610	25,0
Block CAM 70/34	1,1	1,5	8	3,2 - 4,3	30 - 80	290	660	610	26,0
Block BGM 3 *	0,55	0,75	3	1,9 - 3,0	10 - 50	290	660	610	20,0
Block BGM 5 *	0,55	0,75	4,3	2,5 - 3,5	10 - 60	290	660	610	21,0
Block BGM 7 *	0,75	1	5	2,8 - 4,1	20 - 60	290	660	610	22,0
Block BGM 9 *	0,9	1,2	5,6	3,2 - 4,2	20 - 65	290	660	610	23,0
Block BGM 11 *	1,1	1,5	6,5	3,4 - 4,7	20 - 70	290	660	610	25,0

Gsfera\_a\_th

\* Specially suited for suction from buried tanks or wells.

The suction port is threaded Rp 1 1/4 (Rp 1" for PM 16 and PM 30).

The delivery port is threaded Rp 1" for all pumps.

N.B.: After the unit has been installed, the diaphragm tank air precharge must be set to a value 0.2 bar lower than the minimum pressure switch set-point.