DEPURAL[®] TOP

MOBILE FILTER HOUSINGS

DEPURAL® TOP is a range of mobile filter housings especially designed for counter-top use, complete installation kit and diverter valve for easy connection to the tap. The diverter valve make it possible to divert the tap water to the filter or to standard service unfiltered, preserving the filter cartridge and prolonging its life-time.

- DEPURAL® TOP housings are available in 3 main versions:
- DEPURAL® TOP single housings, with clear (TS) white (BW) or chromed (CH) bowls.
- DEPURAL® TOP DUO double housings, with clear (TS) white (BW) or chromed (CH) bowls.

- DEPURAL® TOP TRIO triple housings, with clear (TS) white (BW) or chromed (CH) bowls. DEPURAL® TOP fit to 10" cartridges with both standard SX flat seals (DOE) and BX quick-fit double o-ring end-cap, all available from the wide range of Atlas Filtri cartridges SX and BX type.

DEPURAL® TOP housings are manufactured with the finest and most advanced materials under constant focus on innovative processing technologies and ceaseless modernization to ensure the absolute quality of our products.



cartridges with standard flat seals.







CERTIFICATION



Housings are tested and certified under the most stringent procedures worldwide, in compliance with the sanitary certification EAC/Ghostreghistrazia (Russia).

ACCESSORIES INCLUDED



kit Depural® TOP DVB



kit Depural® TOP ECO



spanner for Depural® TOP



-LUBRIKIT- single-dose lubricant for housing o-ring CODE RE9020650



I

URAL®


WORKING CONDITIONS

| Max working pressure | 3 bar (43 psi) |
|-------------------------|----------------|
| Max working temperature | 45°C (113°F) |
| Min working temperature | 4°C (39,2°F) |
| | |

SPECIFICATIONS


Non-toxic materials, suitable for drinking water. Head: polypropylene. White bowl: SAN. O-rings: EPDM.






DEPURAL® TOP DUO ECO BW WHITE HOUSING CODE:











SPECIFICATIONS

WORKING CONDITIONS

