

PDU20BHVIEC12R/PDU20BHVIEC12Ra
PDU10BVHVIEC20F/PDU20BVHVIEC24F

ENTRY-LEVEL POWER DISTRIBUTION

Provides reliable power distribution for connected equipment

Ideal for server room and IT applications, the Basic PDU Series is a power distribution device that delivers electricity from a single source to multiple devices. The products feature overload protection, external site ground pin, industrial-grade metal housing, adjustable mounting brackets, long input power cord, and cord retention tray.

APPLICATION





- Office
- Back Office
- Server Room
- Data Center
- Factory
- Workstations

SERIES FEATURES

- Overload Protection
- Enclosure Construction
- Industrial-grade Metal Housing
- Cord Retention Tray

PRODUCT CALLOUTS

1. AC Inlet
2. Output Circuit Breaker
3. Ground Stud
4. AC Outlets
5. Cord Retention Tray Screw Holes





TECHNICAL SPECIFICATIONS

Model Name	PDU20BHVIEC12R	PDU20BHVIEC12Ra	PDU10BVHVIEC20F	PDU20BVHVIEC24F
Input				
Nominal Input Voltage (Vac)	200 - 240	200 - 240	200 - 240	200 - 240
Input Frequency (Hz)	50 / 60	50 / 60	50 / 60	50 / 60
Maximum Input Current (A)	16	16	10	16
Input Connector Type	IEC C20 x 1	IEC C20 x 1	IEC C14 x 1	IEC C20 x 1
Power Cord Length (m.)	3.05	3.05	3.05	3.05
Output				
Over Current Protection (Each Bank) (A)	16	16	10	16
Outlets - # of Bank(s) (Bank)	-	1	1	1
Outlet(s) - Total	12	12	20	24
Outlet(s) - Front	-	-	20	24
Outlet(s) - Rear	12	12	-	-
Outlet Type	IEC C13 x 12	IEC C19 x 2, IEC C13 x 10	IEC C19 x 4, IEC C13 x 16	IEC C19 x 4, IEC C13 x 20
Physical				
Installed Rack Height (U)	1	1	0	0
Cord Retention Tray	Yes	Yes	Yes	Yes
Physical Size				
Dimensions (WxHxD) (mm.)	445 x 44.5 x 38.1	445 x 44.5 x 38.1	44.5 x 914.4 x 38.1	44.5 x 1219.2 x 38.1
Weight (kg.)	0.9	0.9	2	2.7
Environmental				
Operating Temperature (°C)	0 - 35	0 - 35	0 - 35	0 - 35
Operating Relative Humidity (Non-condensing) (%)	0 - 95	0 - 95	0 - 95	0 - 95
Certifications				
Certifications*	CE, UL60950	CE, UL60950	CE, UL60950	CE, UL60950
RoHS	Yes	Yes	Yes	Yes

*Certifications may vary according to different regions. Visit www.cyberpower.com for more information.
 #All specifications are subject to change without notice.