



Model		MDOU-12HN1	MDOU-18HN1	
Power supply	V- Ph-Hz	220~240-1-50	220~240-1-50	
Max. input consumption	W	1740	2950	
Max. input current	A	8,5	15,0	
Compressor	Model	PA140G1C-4FT1	PA225X2CS-4KU1	
	Type	Rotary	Rotary	
	Brand	Midea-Toshiba	Midea-Toshiba	
	Capacity	Btu/h	11601	18493
	Input	W	1155	1855
	Rated current (RLA)	A	5,37	8,7
	Locked rotor Amp(LRA)	A	26,7	36,8
	Thermal protector position		Internal	Internal
	Capacitor	uF	35UF/440-450V	50UF/440V-450V
Refrigerant oil	ml	400	750	
Outdoor fan motor	Model	YDK24-6F(B)	YDK48-6H(A)	
	Qty		1	
	Input	W	63	110
	Capacitor	uF	2.5UF/450V	3uF/450V
Speed	r/min	800	890	
Outdoor coil	Number of rows		1	2
	Tube pitch(a) × row pitch(b)	mm	22×19.05	21×13.37
	Fin spacing	mm	1,4	1,4
	Fin type		Hydrophilic aluminum	Hydrophilic aluminium
	Tube outside dia. and type	mm	φ7.94,inner grooved tube	φ7, inner grooved tube
	Coil length×height×width	mm	737×506×19.05	658×546×26.74
Number of circuits		2	2	
Outdoor air flow	m ³ /h	2100	2439	
Outdoor noise level	dB(A)	43	54	
Throttle type		Capillary	/	
Outdoor unit	Dimension (W×D×H)	mm	780×250×547	761×279×593
	Packing (W×D×H)	mm	910×335×575	887×355×645
	Net/ Gross weight	kg	30/32	39/42
Refrigerant type/Quantity	Type		R410A	R410
	Charged volume	kg	0,96	1,4
Refrigerant piping	Liquid side/ Gas side	mm	φ6.4/φ12.7	φ6.4/φ12.7
	Max. pipe length	m	15	25
	Max. difference in level	m	8	15
Ambient temp (Cooling/Heating)	°C	21~43/-5~24	21~43/-5~24	

Remarks:1.The above design and specifications are subject to change without prior notice for product improvement.

2.The values given in the table for the noise level reflect the levels in anechoic chamber.

Model			MDOU-24HN1	MDOU-36HN1
Power supply		V- Ph-Hz	220~240-1-50	380~420-3-50
Max. input consumption		W	3450	4950
Max. input current		A	18	10,0
Compressor	Model		PA290G2CS-4MU1	C-SBN303H8D
	Type		Rotary	Scroll
	Brand		GMCC	Sanyo
	Capacity	Btu/h	24771	33438
	Input	W	2430	3650
	Rated current (RLA)	A	11,65	6,58
	Locked rotor Amp(LRA)	A	66	48
	Thermal protector position		Internal	Internal
	Capacitor	uF	50UF/440V-450V	—
Refrigerant oil	ml	850	1700	
Outdoor fan motor	Model		YDK100-6D	YDK190-6D(B)
	Qty		1	1
	Input	W	167	290
	Capacitor	uF	5UF/450V	10uF/450V
Speed	r/min	900	830	
Outdoor coil	Number of rows		2	2
	Tube pitch(a) × row pitch(b)	mm	21x13.37	21x13.37
	Fin spacing	mm	1,4	1.4
	Fin type		Hydrophilic aluminium	Hydrophilic aluminium
	Tube outside dia. and type	mm	Φ7,inner grooved tube	φ7,inner grooved tube
	Coil length×height×width	mm	785x651x26.74	890x903x26.74
Number of circuits		4	7	
Outdoor air flow		m ³ /h	3200	5000
Outdoor noise level		dB(A)	59	57
Throttle type			Capillary	Capillary
Outdoor unit	Dimension (W×D×H)	mm	842x324x695	990x354x966
	Packing (W×D×H)	mm	965x395x755	1120x435x1100
	Net/ Gross weight	kg	48/54.5	92/96
Refrigerant type/Quantity	Type		R410A	R410A
	Charged volume	kg	1.8	2,9
Refrigerant piping	Liquid side/ Gas side	mm	Φ9.52/Φ15.9(3/8"/5/8")	φ12.7/φ19
	Max. pipe length	m	25	30
	Max. difference in level	m	15	20
Ambient temp (Cooling/Heating)		°C	18~43/-7~24	21~43/-5~24

Remarks:1.The above design and specifications are subject to change without prior notice for product improvement.

2.The values given in the table for the noise level reflect the levels in anechoic chamber.

Model			MDOU-48HN1	MDOU-60HN1
Power supply		V- Ph-Hz	380~415-3-50	380~415-3-50
Max. input consumption		W	6300	7500
Max. input current		A	10,5	12,6
Compressor	Model		C-SBN373H8D	C-SBN453H8D
	Type		Scroll	Scroll
	Brand		Sanyo	Sanyo
	Capacity	Btu/h	48109	55956,8
	Input	W	4750	5750
	Rated current (RLA)	A	8,22	9,77
	Locked rotor Amp(LRA)	A	66	67
	Thermal protector position		Internal	Internal
	Capacitor	uF	-	/
Refrigerant oil	ml	1700	1700	
Outdoor fan motor	Model		YDK65-6/YDK65-6F	YDK65-6/YDK65-6F
	Qty		2	2
	Input	W	148+156	148+140
	Capacitor	uF	(3.5UF/450V)×2	(3.5UF/450V)×2
Speed	r/min	800	800	
Outdoor coil	Number of rows		2	2
	Tube pitch(a) × row pitch(b)	mm	21×13.37	22×19.05
	Fin spacing	mm	1,4	1,6
	Fin type		Hydrophilic aluminium	Hydrophilic aluminium
	Tube outside dia. and type	mm	φ7 inner grooved tube	φ7.94,inner grooved tube
	Coil length×height×width	mm	840×1113×26.74	837×1100×38.1
	Number of circuits		4	8
Outdoor air flow	m ³ /h	6800	6850	
Outdoor noise level	dB(A)	59	59,3	
Throttle type		Capillary	Capillary	
Outdoor unit	Dimension (W×D×H)	mm	900×340×1167	900×340×1167
	Packing (W×D×H)	mm	1032×443×1307	1032×443×1307
	Net/ Gross weight	kg	102/106	106/111
Refrigerant type/Quantity	Type		R410A	R410A
	Charged volume	kg	3,25	3,2
Refrigerant piping	Liquid side/ Gas side	mm	φ12.7/φ19	φ12.7/φ19
	Max. pipe length	m	50	50
	Max. difference in level	m	25	25
Ambient temp (Cooling/Heating)	°C	21~43/-5~24	21~43/-5~24	

Remarks:1.The above design and specifications are subject to change without prior notice for product improvement.

2.The values given in the table for the noise level reflect the levels in anechoic chamber.